NO SCREW STF-C64A

- · Designed to allow front operation.
- · Locks when fastened to prevent accidental

Ø4.5

Carton (pcs)

210

- release.

 Pull lever and lift latch to open.
- Door thickness : 14~28 mm (9/16"~1-1/8")

•STF-C64A					
L (mm)	Clamping Force kgf±1.5 (lbs±3.3)				
40	0				
41	6.0 (13.2 lbs)				
42	7.3 (16.0 lbs)				
43	8.6 (19.0 lbs)				
44	9.9 (21.8 lbs)				

*Maximum"L"dimension is 44 mm.

-	Material	Finish
	304 Stainless Steel	Polished



COMPACT DRAW LATCH

Spring

With

CORNER FASTENER (W/LOCK)

(39.5)

+ 18 (45/6

Hole for Sealing Pin

00

16

Weight (g)


66.5

ock Release Lever

Hole for pad lock

Box (pcs)

15



Adjust latch distance by turning arm.				

SCC-TF30 304 NO SCREW

- Compact size.
- · Adjustable arm latch.
- · Screw not included. Recommended screw size M3.
- · Provides consistent hold tension for secure latching.

No.	Part Name	Material			
1	Base	304 Stainless Steel			
2	Latch Plate	Stainless Steel			
3	Lever	304 Stainless Steel			
4	Rotating Pin	303 Stainless Steel			
(5)	Adjustment Shaft	SUS Stall liess Steel			
6	Counterplate	304 Stainless Steel			

					~	
Item No.	Load Capacity (kg)	Weight (g)	Box (pcs)	Carton (pcs)	(5)	Adjustm
SCC-TF30	51 (112 lbs)	32	100	400	6	Count

CORNER FASTENER



Designed to allow front operation.Available in two different counterplate styles. (39) (39)15.5 15.5 40.518 (39.5) (39.5)* 2 2 STF-A56AC 1.5 25 2-Ø4.5 - 9 (17) Ø4.5 Finish STF-A56AH *Dimensions shown are for clamping force of "0"




304 Stainless Steel		Polished				
Item No. Weight (it (g)	Box (pcs)		Carton (pcs)	
STF-A56AH	56		100		1000	
STF-A56AC	50)	100		1000	

Material

www.sugatsune.com

STF-A56AH, AC





CATCHES & LATCHES

STF-C64A

Item No.

STF-C64A