SUGATSUNE

CONCEALED HINGE (W/REMOVABLE PIN)




Concealed hinge with removable pin.For sheet metal use.



TS-243-30S

TS-243-30




| Ite | m No. | Load Capacity (kgf/2pcs) | t | d | е | Weight (g) | Material | Box (pcs) |
|------|---------|--------------------------|-----|--------------|-----|------------|---------------------|-----------|
| TS-2 | 243-30S | 34 (74.8 lbs) | 3.0 | Ø 7.4, φ12.8 | 6.1 | 34 | 304 Stainless Steel | 30 |
| TS-2 | 243-30 | 28 (61.6 lbs) | 3.2 | Ø 6.8, φ12.8 | 6.3 | 28 | Steel | 30 |

BUTT HINGE (W/SPRING)



Spring loaded to keep doors closed.
Sucessfully passed one million open/ close cycling test.





| Æ | | | | | | | | | |
|------|------|-----|---------------|-----------|---------------|-------------|--|--|--|
| × | | No. | Part Name | e | Material | Finish | | | |
| / | ×. | 1 | Body 1 | | 304 Stainless | Polished | | | |
| (96) |)° | 2 | Body 2 | | 304 Stainless | Folished | | | |
| | | 3 | Collar Washer | | 303 Stainless | - | | | |
| | | 4 | Spring | | 304 Stainless | - | | | |
| | | 6 | Shaft | | 303 Stainless | - | | | |
| | | | | | | | | | |
| н | Р | | Weight (g) | Box (pcs) | | Carton (ps) | | | |
| 32 | 18 | | 20 | | | | | | |
| 50 | 0 32 | | 30 | | 50 | 500 | | | |
| 0 40 | | | 20 | 1 | | | | | |

| | | | 6 | Snan | 303 Stainless | Steel | - |
|----------------------------|------------------|---|--|---|---|---|---|
| | (0) | | | 14 (1 + () | D () | 0 | 1 () |
| kgf·cm)l Load Capacity (k | gf/2pcs) H | Р | | Weight (g) | Box (pcs) | Ca | rton (ps) |
| •in) 4 (8.8 lbs | s) 32 | 18 | | 20 | | 500 | |
| in) € (12.2 lb) | 50 | 32 | | 30 | 50 | | |
| •in) 6 (13.2 ID | 60 | 40 | | 38 | | | |
| | ·in) 4 (8.8 lbs | in) 4 (8.8 lbs) 32 ·in) 6 (13.2 lbs) 50 | in) 4 (8.8 lbs) 32 18 in) 6 (13.2 lbs) 50 32 | Load Capacity (kgf/2pcs) H P ·in) 4 (8.8 lbs) 32 18 ·in) 6 (13.2 lbs) 50 32 | Image: Ggf-cm)l Load Capacity (kgf/2pcs) H P Weight (g) ·in) 4 (8.8 lbs) 32 18 20 ·in) 6 (13.2 lbs) 50 32 30 | Image: Gpf-cm)l Load Capacity (kgf/2pcs) H P Weight (g) Box (pcs) -in) 4 (8.8 lbs) 32 18 20 -in) 6 (13.2 lbs) 50 32 30 50 | ini) 6 (13.2 lbs) 50 32 30 50 |

