MINI GUIDE BLOCK & RAIL

RoHS compliant · ALUMINUM · NO SCREW

MRS20, MR-20CS

MR-20CS

- Perfect for small stroke application.
- No lubricant (P. 415,416,417) needed.

* Block and Rail sold separately.





Installation



MR-20CS



■ Rail

25.4 mm=1"

Item No.	L	N	Weight (g)	Box (pcs)
MRS20-100	3-15/16" (100 mm)	2	20	200
MRS20-200	7-7/8" (200 mm)	4	40	
MRS20-400	15-3/4" (400 mm)	8	80	100
MRS20-800	31-1/2" (800 mm)	16	160	80
MRS20-2000	78-3/4" (2000 mm)	40	400	30

*Both ends of rail are not anodized.

No.	Material	Finish
①	Polyethylene (UL 94HB)	Grey
②	304 Stainless Steel	Plain
③	Aluminum	Anodized

■ Block

Item No.	Weight (g)	Box (pcs)	Carton (pcs)
MR-20CS	6	50	1000

MRS 20, MR-20CS LOAD RATING INFORMATION





Horizontal Static Load Fx	67.5 lbs (30.6 kg)
Vertical Static Load Fy	39.2 lbs (17.8 kg)

◆ Reduction Factor

Certain reduction needs to be applied depending on application or environment.
Low speed/Low operation frequency = 70% to 100% of Load Rating
Moderate speed/High operation frequency = 35% to 65% of Load Rating
High operation frequency with Vibration & Shocks = 10% to 30% of Load Rating